

# Kasura

#### Swivel chair low back 92015

Overall dimensions  $25"w \times 25.5"d \times 31.5"h$  (4-Prong swivel) Weight 34 lbs.  $29"w \times 29"d \times 31/35"h$  (5-Prong swivel)

Seat dimensions 19"w x 19"d x 18"h (4-Prong swivel) Cubic feet 17

19"w x 19"d x 18/22"h (5-Prong swivel)

Seat to top of back 15.75" COM 1.75 yds.(seat, inside back)

1.75 yds.(outside back) Top of arm to floor 25.5" (4-Prong swivel) COL 35 sq. ft.(seat, inside back)

25.5/29.5" (5-Prong swivel) 35 sq. ft.(outside back)

Top of arm to seat



## Swivel chair mid back 92016

Overall dimensions	25"w x 26.5"d x 36.75"h (4-Prong swivel) 29"w x 30"d x 36.5/40.5"h (5-Prong swivel)	Weight	36 lbs.	
Seat dimensions	19"w x 19"d x 18"h (4-Prong swivel) 19"w x 19"d x 18/22"h (5-Prong swivel)	Cubic feet	25	
Seat to top of back	21.25"	СОМ	2 yds.(seat, inside back) 1.75 yds.(outside back)	

40 sq. ft.(seat, inside back) Top of arm to floor 25.5" (4-Prong swivel) COL 25.5/29.5" (5-Prong swivel) 35 sq. ft.(outside back)

8" Top of arm to seat



#### Swivel chair high back 92017

Overall dimensions	25"w x 26.5"d x 48"h (4-Prong swivel) 29"w x 31"d x 47.5/51.5"h (5-Prong swivel)	Weight	39 lbs.	
Seat dimensions	19"w x 19"d x 18"h (4-Prong swivel) 19"w x 19"d x 18/22"h (5-Prong swivel)	Cubic feet	25	/\\\\\\
Seat to top of back	31.5"	СОМ	2.25 yds.(seat, inside back) 1.75 yds.(outside back)	
Top of arm to floor	25.5" (4-Prong swivel) 25.5/29.5" (5-Prong swivel)	COL	45 sq. ft.(seat, inside back) 35 sq. ft.(outside back)	
Top of arm to seat	8"			

Standard features	Optional features
<ul> <li>Upholstered interior and upper back</li> <li>Molded back and seat foam</li> <li>Swivel tilt mechanism with forward lock position</li> </ul>	Base - 4 - Prong swivel with return to center and stationary glides - 5 - Prong swivel with pneumatic lift for height adjustment and standard or hardwood casters  Base finish - 4 - Prong: polished aluminum, standard/studio paints - 5 - Prong: polished aluminum or onyx  Outside back

### Standard textile & finish selection

	https://ofs.com/resources/textiles http://ofs.com/resources/finishes				
Frame construction					
Frame	Steel tube frame covered in molded foam				
Unholstory	All fabric and leather pieces are cut with automated cutters that utilize precise patterns				

Upholstery · All fabric and leather pieces are cut with automated cutters that utilize precise patterns

Assembly · Metal and foam components fastened by bolts with thread locker

### Outside back trim panel

Molded plywood · Upholstered, painted or finished veneer

#### Foam

Seat • 3" Thick premium grade foam

- 46 lb. Compression
- 3 lb. Density

• Various thicknesses of premium grade molded foam Back

- 51 lb. Compression
  - 3 lb. Density

ofs.com imagine a place® 800.521.5381 Spec sheet 1 of 1