



Finish Selection

- Veneer
 - Flat cut veneers are Oak and Walnut
 - Quartered cut veneers are Oak, Walnut, Desert and Oslo
 - Studio Veneers: only offered on run-off tops are Salvage Linen and Salvaged Root
 - All veneers have a supermatter clear finish

- Laminate
 - OFS standard solid laminates: Black, Frosty White, Grey, Pure White and Slate Grey
 - Additional solid laminates - Aqua Lagoon, Burgundy, Summer Vacation, Sunray and Woodvine

Construction

- Beam to post connection is done with bolts, steel mounting plates and insert nuts.
No wood screw connections, units can be disassembled and reassembled as needed.
Adjustable levelers

- Posts
 - Pressed maple plywood skinned with veneer and glued to solid hardwood lumber rails
 - Veneer or HPL face and back with exposed maple plywood edge and solid wood core
 - Oak veneer gets oak lumber core
 - Walnut veneer gets walnut lumber core
 - HPL gets beech lumber core
 - Hollow core allows wire management through post
 - Corner post
 - Creates a 90 degree connection
 - 3-way post
 - Creates a 3 way connection at 90 and 180 degrees
 - 4-way post
 - Creates a 4 way connection at 90 degree increments

- Beam
 - Extruded aluminum with steel mount plates
 - Open & framed wall kits
 - Full wall rail kits
 - Table wall rail kits
 - Center roof beam kits

- Beam Cladding
 - Particleboard core with veneer or HPL faces with plywood edge veneer

- Roofs
 - Attaches to beam extrusions
 - Baffle roof panel design
 - Veneer - PBD core with veneer faces with matching EVN
 - HPL - PBD core with HPL faces with matching 1mm PP
 - PET - pressed polyethylene terephthalate
 - Metal frame: aluminum inner support rail with steel outer sleeve spacers powder coated with steel attachment plates

- Framed Panels
 - MDF with veneer skins for outer frame for all infill types, butt-joint connection
 - Machined slat wall panel - machined plywood core with veneer or HPL skin
 - Metal infill wall panel: 1 1/2" x 1/2" steel frame welded to metal infill skin and powdercoated
 - Wire Mesh - 10ga wire with 3" square grid pattern
 - Performance metal - 1/2" diameter holes with 1/16" staggered offset
 - Split infill wall panel
 - Veneer - PBD core with veneer faces
 - HPL - PBD core with HPL faces
 - Acrylic - 1/4" clear or frosted acrylic
 - PET - pressed polyethylene terephthalate

- Full Wall Panels
 - Veneer - PBD core with veneer faces and 3mm EVN
 - HPL - PBD core with HPL faces with 3mil matching edge banding
 - Fabric - MDF core with fabric face
 - Cork - PBD core with 1/4" cork face with 3mm black edge banding
 - Markerboard - PBD core with white markerboard HPL face with 3mm FW2 edge banding

- Split Wall Panels
 - Veneer - PBD core with veneer faces and 3mm EVN
 - HPL - PBD core with HPL faces with 3 mm matching edge banding
 - Fabric - MDF core with fabric face
 - Cork - PBD core with 1/4" cork face with 3mm black edge banding
 - Markerboard - PBD core with white markerboard HPL face and with 3mm FW2 edge banding

Curtains

- Static Panel Curtain - attaches underneath beam to trim rail
- Sliding Folding Curtain - hangs from steel track recessed into beam trim rail



Power

- Post Power Sleeve - allows power receptacles in face of a post corner
- 4 trac power - 4 wire two circuit system

Worksurfaces

- Veneer, HPL, and solid surface
- 1.125"thick
- 3 ply construction
- Flat knife edge profile user edges
 - Wedge
 - Sweep
 - Rectangular
 - Run-off
 - Table wall worksurface (rectangular)

Planters

- Tennon and groove construction