



Finish selection

- Veneer
 - Flat cut veneers are Oak and Walnut
 - Quartered cut veneers are Oak, Walnut, Desert, and Oslo
 - Studio veneers: only offered on run-off tops are Salvage Linen and Salvaged Root
 - All veneers have a super matte clear finish

- Laminate
 - OFS standard solid laminates: Black, Frosty White, Grey, Pure White, and Slate Grey
 - Additional solid laminates - Aqua Lagoon, Burgundy, Summer Vacation, Sunray, and Woodvine

Construction

- Beam to post connection is done with bolts, steel mounting plates and insert nuts.
No wood screw connections, units can be disassembled and reassembled as needed.
Adjustable levelers

- Posts
 - Pressed maple plywood skinned with veneer and glued to solid hardwood lumber rails
 - Veneer or HPL face and back with exposed maple plywood edge and solid wood core
 - Oak veneer gets oak lumber core
 - Walnut veneer gets walnut lumber core
 - HPL gets beech lumber core
 - Hollow core allows wire management through post
 - Corner post
 - Creates a 90 degree connection
 - 3-way post
 - Creates a 3 way connection at 90 and 180 degrees
 - 4-way post
 - Creates a 4 way connection at 90 degree increments

- Beam
 - Extruded aluminum with steel mount plates
 - Open and framed wall kits
 - Full wall rail kits
 - Split wall rail kits
 - Table wall rail kits
 - Center roof beam kits
 - Bench/perch wall rail kits

- Beam cladding
 - Particleboard core with veneer or HPL faces with plywood edge veneer

- Roofs
 - Attaches to beam extrusions
 - Baffle roof panel design
 - Veneer - PBD core with veneer faces with matching EVN
 - HPL - PBD core with HPL faces with matching 1mm PP
 - PET - pressed polyethylene terephthalate
 - Metal frame: aluminum inner support rail with steel outer sleeve spacers powder coated with steel attachment plates

- Framed panels
 - MDF with veneer skins for outer frame for all infill types, butt-joint connection
 - Machined slat wall panel - machined plywood core with veneer or HPL skin
 - Metal infill wall panel: 1 1/2" x 1/2" steel frame welded to metal infill skin and powder coated
 - Wire Mesh - 10ga wire with 3" square grid pattern
 - Performance metal - 1/2" diameter holes with 1/16" staggered offset
 - Split infill wall panel
 - Veneer - PBD core with veneer faces
 - HPL - PBD core with HPL faces
 - Acrylic - 1/4" clear or frosted acrylic
 - PET - pressed polyethylene terephthalate
 - Acoustic infill wall panel
 - Face and back panels covered with a layer of sound reducing acoustic material then wrapped in choice of fabric
 - Inner wall cavity filled with denim batt material

- Full wall panels
 - Veneer - PBD core with veneer faces and 3mm EVN
 - HPL - PBD core with HPL faces with 3mm matching edge banding
 - Fabric - MDF core with fabric face
 - Cork - PBD core with 1/4" cork face with 3mm black edge banding
 - Markerboard - PBD core with white markerboard HPL face with 3mm FW2 edge banding



- Split wall panels
- Veneer - PBD core with veneer faces and 3mm EVN
 - HPL - PBD core with HPL faces with 3 mm matching edge banding
 - Fabric - MDF core with fabric face
 - Cork - PBD core with ¼" cork face with 3mm black edge banding
 - Markerboard - PBD core with white markerboard HPL face and with 3mm FW2 edge banding

Lights

- Anodized light bars available in four colors
- Dimmable LED's
- Motion sensor for auto off
- Self powered wireless switch for manual on/off, dimming
- Kits are synced so all lights with unit work on same switch

Glass

- Anodized aluminum extrusions, hardware, and powder coated steel thresholds available in Satin, White, and Oiled Bronze
- ½" Thick clear glass panels
- Full wall and door wall options
- Ladder pull and lever latch options on the door

Coat hook

- Solid lumber available in ASH or WAL

Bag knob

- Solid lumber available in ASH or WAL
- Determined by post finish

Curtains

- Sliding folding curtain - hangs from steel track recessed into beam trim rail

Power

- Post power sleeve - allows power receptacles in face of a post corner
- 4 trac power - 4 wire two circuit system
- Full wall panel duplex receptacle power options

Worksurfaces

- Veneer, HPL, and solid surface
- 1.125" Thick
- 3 ply construction
- Flat knife edge profile user edges
 - Wedge
 - Sweep
 - Rectangular
 - Run-off
 - Table wall worksurface (rectangular)
 - Delta
 - T shape
 - S shape
 - Island
 - Supported wedge
 - Supported rectangle

Planters



- Tennon and groove construction

Bench cushion

- | | |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame construction | Fully upholstered <ul style="list-style-type: none">• Seat - construction grade plywood• Upholstery - all fabric pieces are cut with automatic cutters that utilize precise patterns• Assembly - mounted with steel brackets and screws |
| Foam | <ul style="list-style-type: none">• 1.75" Premium grade foam• 50 lb. Compression• 2.3 lb. Density |
| Tablet | <ul style="list-style-type: none">• Post available in all standard and studio powder coats• Tablet available in all standard Obeya veneers and HPL's• OB-84BC will have one tablet when option is selected• OB-126BC will have two tablets when option is selected |

Perch cushion

- | | |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame construction | Fully upholstered <ul style="list-style-type: none">• Seat - molded plywood and construction grade plywood• Upholstery - all fabric pieces are cut with automatic cutters that utilize precise patterns• Assembly - secured with wooden panel |
| Foam | <ul style="list-style-type: none">• 1.5" Premium grade foam• 50 lb. Compression• 2.3 lb. Density |