Range building blocks

OFS

Table of contents

Bench kit

- Widths: 54″w, 60″w, 66″w, 72″w
- Includes height adjustable legs, top racks, cross bars, digital control panel, control box and cables
- Worksurfaces, cable carrier, ganging kits and privacy panels ordered separately

- Creep factor is accounted for in frame size when ganging benches
- Ships KD
- Accommodates two users

HB-_ _HABK

Bench kit Components

Cable carrier

- Widths: 54″w, 60″w, 66″w, 72″w
- Stores and conceals electrical and data
- Available with no power, three circuit (five wire) or four circuit (eight wire) power option
- When power option is selected, carrier includes power block assembly with four outlets for each user
- Supports rail mounted privacy panel
- **Note**: Duplex receptacles, power in-feeds and jumpers not included

End cap

- Use to finish end of benching run on cable carrier
- Set of two

Cable entry pole

- Conceals power and data from floor to bench
- Removable panel for cable access

Ganging kit

- Use to gang bench kits together
- Ganging tray used for bench kits with cable carriers
- Ganging rail used for bench kits with no cable carriers

Cable carrier
HB-_ _ CC

End cap
HB-EC

Cable entry pole
HB-CEP

Ganging tray
HB-GKT

Ganging rail
HB-GKR

Bench kit Worksurfaces

General

• Depths: 24"d, 30"d

• Worksurface shapes: Rectangle or soft rectangle. 4" radius on corners

Standard worksurfaces

• Not for use with side mount modesty panels

• 52"w, 58"w, 64"w, 70"w

• Worksurfaces are 2" shorter than bench kit nominal width

Worksurface for side edge modesty

• 48"w, 54"w, 60"w, 66"w

• Worksurfaces are 6" shorter than overall bench kit nominal width to allow for depth of privacy panel, and 1.5" wire management gap on each side

Standard worksurface

Worksurface with side edge modesty

Rectangle worksurface
24"d

HB-_ _24HART - no side modesty
HB-_ _24HARTS - with side modesty

Rectangle worksurface
30"d

HB-_ _30HART - no side modesty
HB-_ _30HARTS - with side modesty

Soft rectangle worksurface
24"d

HB-_ _24HASRT - no side modesty
HB-_ _24HASRTS - with side modesty

Soft rectangle worksurface
30"d

HB-_ _30HASRT - no side modesty
HB-_ _30HASRTS - with side modesty

Bench kit Rail mount privacy screens

General

- Widths: 40″w (54″w bench kit), 46″w (60″w bench kit), 52″w (66″w bench kit), 58″w (72″w bench kit)
- Heights: 21.75″h (creates overall height of 42″h) or 27.75″h (creates overall height of 48″h)
- For double sided applications
- Mounts directly to cable carrier, includes post mount brackets
- Material: TFL or HPL laminate (horizontal grain), veneer (vertical grain), or fabric (tackable)

Square corner screen

- For COM square fabric screen, fabric roll must be 48″w minimum for 21.75″h screens and 54″w minimum for 27.75″h screens, and cut railroaded

Laminate, square corner

HB-_ _ _22LP
42″ overall height

HB-_ _ _28LP
48″ overall height

Laminate, round corner

HB-_ _ _22LPR
42″ overall height

HB-_ _ _28LPR
48″ overall height

Veneer, square corner

HB-_ _ _22WP
42″ overall height

HB-_ _ _28WP
48″ overall height

Veneer, round corner

HB-_ _ _22WPR
42″ overall height

HB-_ _ _28WPR
48″ overall height

Fabric, square corner

HB-_ _ _22FP
42″ overall height

HB-_ _ _28FP
48″ overall height

Bench kit Divider wall privacy panels

- Widths: 36"w, 42"w, 48"w, 54"w, 59"w
- Heights: 42"h, 48"h
- Mounts directly to bench kit to create end of run privacy. Includes mounting brackets

- Available as square, or with 3" radius rounded corners
- Material: TFL or HPL laminate, or veneer
- Vertical grain direction for all materials

Square corner

HB-42_ _DW (42"h)

HB-48_ _DW (48"h)

Round corner

HB-42_ _DWR (42"h)

HB-48_ _DWR (48"h)

Bench kit End of run modesty

- Width: 32.75"w
- Height: 13.5"h
- Mounts directly to bench kit to create end of run privacy. Includes mounting brackets

- Available as square, or with 3" radius rounded corners
- Material: TFL or HPL laminate, or veneer
- Vertical grain direction for all materials

Square corner

HB-1433EM
42"height

Round corner

HB-1433EMR
42" overall height

Height adjustable desk Bases

- Offset freestanding height adjustable base
- Widths: 48″w, 54″w, 60″w, 66″w, 72″w
- Depths: 24″d or 30″d
- Includes height adjustable legs, feet, top racks, digital control panel, control box and cables
- Glides standard, optional casters available
- Accommodates one user

- Worksurface, privacy panel and wire management ordered separately. **Note**: Must be used with height adjustable desk worksurface
- **Note:** Worksurface edge privacy panel cannot be used on 24″d worksurfaces
- Ships KD

24″d

HB-_ _24FSE

30″d

HB-_ _30FSE

Height adjustable desk Worksurfaces

- Widths: 48″w, 54″w, 60″w, 66″w, 72″w
- Depths: 24″d or 30″d
- Worksurface shapes: Rectangle and soft rectangle. 4″ radius on corners

- Privacy panel and wire management ordered separately
- **Note:** Worksurface edge privacy panel cannot be used on 24″d worksurfaces

24″d rectangle

HB-_ _24HART

30″d rectangle

HB-_ _30HART

24″d soft rectangle

HB-_ _24HASRT

30″d soft rectangle

HB-_ _30HASRT

OFS

Privacy screens Worksurface edge mount, bench kit

General

- Height: 22.5"h (18" above and 3" below worksurface)
- Widths: 50"w, 56"w, 62"w, 68"w
- Screen is 2" shorter than worksurface width. Use with 52"w, 58"w, 64"w and 70"w worksurfaces
- Requires four brackets
- Leaves a 1.5"w gap between modesty panel and worksurface edge for wire management
- Available as square or rounded corners
- Material: Frosted acrylic, TFL or HPL laminate (horizontal grain), veneer (vertical grain), or fabric (tackable)
- **Note:** ET_ _ modesty trim recommended to be used with acrylic worksurface edge modesty to prevent warping or bowing

Round corner screen

- 3" round corners
- Rounded fabric screen available in twelve solid knit fabrics (tackable)

Screen brackets

- Use WEBKT-1 for acrylic edge worksurface modesty panels
- Use WEBKT-2 for TFL and veneer edge worksurface modesty panels
- Use WEBKT-3 for fabric edge worksurface modesty panels

Square corner

Acrylic	Laminate	Veneer	Fabric
HB-WEMA-_ _/22.5	HB-WEMK-_ _/22.5	HB-WEMW-_ _/22.5	HB-WEMF-_ _/22.5

Round corner

Acrylic	Laminate	Veneer	Fabric
HB-WEMAR-_ _/22.5	HB-WEMKR-_ _/22.5	HB-WEMWR-_ _/22.5	HB-WEMFR-_ _/22.5

Screen brackets

Acrylic bracket	Laminate bracket	Fabric bracket
WEBKT-1	WEBKT-2	WEBKT-3

Privacy screens Worksurface edge mount, height adjustable desk

General

• Height: 22.5"h (18" above and 3" below worksurface)

• Widths: 46"w, 52"w, 58"w, 64"w, 70"w

• Screen is 2" shorter than worksurface width. Use with 48"w, 54"w, 60"w, 66"w and 72"w worksurfaces

• Requires four brackets

• Leaves a 1.5"w gap between modesty panel and worksurface edge for wire management

• Material: Frosted acrylic, TFL or HPL laminate (horizontal grain), veneer (vertical grain), or tackable fabric

• **Note:** ET_ _ modesty trim recommended to be used with acrylic worksurface edge modesty to prevent warping or bowing

• **Note:** Screen cannot be used with 24"d worksurface

Round corner screen

• 3" round corners

• Rounded fabric screen available in twelve solid knit fabrics (tackable)

Screen brackets

• Use WEBKT-1 for acrylic edge worksurface modesty panels

• Use WEBKT-2 for TFL and veneer edge worksurface modesty panels

• Use WEBKT-3 for fabric edge worksurface modesty panels

Square corners

Acrylic
HB-WEMA-_ _/22.5

Laminate
HB-WEMK-_ _/22.5

Veneer
HB-WEMW-_ _/22.5

Fabric
HB-WEMF-_ _/22.5

Round corners

Acrylic
HB-WEMAR-_ _/22.5

Laminate
HB-WEMKR-_ _/22.5

Veneer
HB-WEMWR-_ _/22.5

Fabric
HB-WEMFR-_ _/22.5

Screen brackets

Acrylic bracket
WEBKT-1

Laminate bracket
WEBKT-2

Fabric bracket
WEBKT-3

Privacy screens Side edge modesty

- Height: 22.5"h (18" above and 3" below worksurface)
- Widths: 23"w, 29"w
- Use along worksurface depth
- Requires two WEBKT-1 brackets
- Frosted acrylic only
- Square or 3" round corners

- **Note:** Recommended to be used with worksurface edge modesty trim to prevent warping or bowing
- Leaves a 1.5"w gap between modesty panel and worksurface edge for wire management

Rail screen shown at overall height of 42"

Square
HB-WEMA-_ _/22.5

Round
HB-WEMAR-_ _/22.5

Privacy screens Acrylic trim

- Widths: 23"w, 29"w, 46"w, 50"w, 52"w, 56"w, 58"w, 62"w, 64"w, 68"w
- Trim is ⅛" shorter than screen width

- Attaches to top edge of acrylic panel to keep panel straight
- Clear anodized aluminum finish

ET_ _

Privacy screens Worksurface set on

- Height: 11"h
- Widths: 24"w, 30"w
- ¾" thick panel, total depth 4" with fixed brackets
- Rests along worksurface depth
- Square or round corners

- Material: TFL, HPL laminate, or veneer (all vertical grain), or fabric (tackable)
- Rounded fabric screen available in twelve solid knit fabrics (tackable)

Square corners
Rail screen at overall height of 42"

Laminate
WS-WEMK-_ _/11

Veneer
WS-WEMW-_ _/11

Fabric
WS-WEMF-_ _/11

Round corners
Rail screen at overall height of 48"

Laminate
WS-WEMKR-_ _/11

Veneer
WS-WEMWR-_ _/11

Fabric
WS-WEMFR-_ _/11

Hanging drawer

- Height: 6.125"h
- Width: 17.375"w
- Depth: 10.5"d
- Use with stand alone height adjustable tables

- Upper tray drawer
- Lower open paper shelf
- Not recommended for tops less than 60"w
- Optional PET pencil tray

HDS

Electrical 3 circuit/5 wire

- Infeed options include: liquid tight, metal, NYC code and plug and play. Liquid and metal infeeds are 10′, NYC code and plug and play infeeds are 6′ long. **Note**: Plug and play infeed requires 20 Amp wall outlet, and limits system to all circuit I duplexes

- Jumper used to connect powered cable carriers when ganged
- Duplexes available in circuit I, II and III

Liquid tight infeed
PWF5L120

Metal infeed
PWF5M120

Metal infeed - NYC code
PWF5NYC

Plug and play infeed
PWF5M20AMP

Power jumper
MCJ5W38M

Y block
YCB5

Duplex
DPX5W_

Electrical 4 circuit/8 wire

- Infeed options include: liquid tight, metal, NYC code and plug and play. Liquid and metal infeeds are 10′, NYC code and plug and play infeeds are 6′ long. **Note**: Plug and play infeed requires 20 Amp wall outlet, and limits system to all circuit I duplexes
- Jumper used to connect powered cable carriers when ganged

- Duplexes with 15 amp circuit available in circuit I, II, III and IV (isolated and dedicated)
- Title 24: Duplexes with 15 amp circuit for Title 24 power requirements. Circuits I, II, III, or IV (isolated and dedicated)

Liquid tight infeed
PWF3L120

Metal infeed
PWF3M120

Metal infeed - NYC code
PWF3NYC

Plug and play infeed
PWF3M20AMP

Power jumper
MCJ8W38M

Duplex
DPX8W_

Duplex - Title 24
DPX8WCT_

Wire management

- WM-V4 Velcro wire manager strip comes in pack of four, not intended for heavy duty cabling

- Plastic wire manager: Use under worksurface. Widths include 12″w, 24″w, 36″w, 48″w, 60″w, 72″w. Can be field cut

- Wire basket manager: Use under worksurface. Widths include 18″w, 33″w, 57″w

- Cable management clip mounts under worksurface, three position clip

- WM-HA height adjustable wire manager commonly used in stand alone height adjustable table applications

- WM-HA_ height adjustable wire manager is commonly used in table to table connections. WM-HA3 is silver/silver combination, WM-HA4 is black/black combination, WM-HA5 is white/white combination

- WM-HA6 is fabric wire manager fastened with Velcro

Velcro wire manager
WM-V4

Plastic wire manager
WM-_ _

Wire basket manager
WBT__H

Cable clip
CM30-NR

Height adjustable
table desk manager
WM-HA

Height adjustable
table to table manager
WM-HA_

Fabric wire manager
WM-HA6

Power supplies

Clamp on power

- PS-62W: Two outlets, two USB charging ports

- PS-63W: Three outlets, two USB charging ports

Clamp mount

PS-62W

PS-63W