

Edge



Square

Standard textile & finish selection

<https://ofs.com/resources/textiles>
<https://ofs.com/resources/finishes>

Worksurfaces

- 1" thick TFL, HPL, or veneer
- TFL worksurfaces are thermally-fused with a 2mm polypropylene edge
- HPL worksurfaces are 3-ply construction with a 2mm polypropylene edge
- Veneer worksurfaces are 3-ply construction with a 2mm wood edge

Bases

- | | |
|-----------|--|
| Bench kit | <ul style="list-style-type: none"> • Accommodates two users per section • Height adjustable range: 24.875"h-50.5"h • Powder coated metal frame in black or grey • Glides offer 1/2" adjustment |
| Frame kit | <ul style="list-style-type: none"> • Accommodates one user • Freestanding height adjustable worksurface • Height adjustable range: 23.625"h-49.75"h |

Electrical

- | | |
|---------------|--|
| Circuit types | <ul style="list-style-type: none"> • Cable carrier standard as pass through with no electrical cutouts • 3 circuit/5 wire • 4 circuit/8 wire • Chicago code • UL listed electrical components |
| Data | <ul style="list-style-type: none"> • Data knock outs on underside of cable carrier |

Hanging drawer

- Plywood drawer
- Drawer sides and backs are .5" thick
- Drawer bottoms: Tray drawer .125" thick, Box and file drawers .25" thick
- Drawer front is field replaceable