

## Mesh mid back stool 619

<b>Overall dimensions</b>	27.5"w x 27.5"d x 42/49.25"h (CHC) 27.5"w x 27.5"d x 45.5/55.75"h (BHC)	<b>Weight</b>	51.25 lbs. armless 60.25 lbs. arms (CHC) 52.25 lbs. armless 61.25 lbs. arms (BHC)
<b>Seat dimensions</b>	21"w x 19"d x 20/27.25"h (CHC) 21"w x 19"d x 23.5/33.75"h (BHC)	<b>Cubic feet</b>	12.75
<b>Seat to top of back</b>	22"	<b>COM</b>	1 yd.
<b>Back width</b>	20.25"	<b>COL</b>	20 sq. ft.
<b>Top of arm to floor</b>	CHC: 29.25/37.25" (CR14), 28.5/36.5" (CR16), 28.25/39.25" (CR11, CR17) 27.75/38.75" (CR12, CR18) BHC: 32.75/42.75" (CR14), 32/42" (CR16), 31.75/45.75" (CR11, CR17) 31.25/42.25" (CR12, CR18)		
<b>Top of arm to seat</b>	8" (CR14), 7" (CR16), 6.5/10.25" (CR11, CR17), 6/9.75" (CR12, CR18)		



Standard features	Options available
<ul style="list-style-type: none"> <li>• Mid back</li> <li>• Armless</li> <li>• 3D Lined mesh back</li> <li>• Upholstered seat with molded seat foam</li> <li>• Black nylon base</li> <li>• Hard wheel casters</li> <li>• 20" Foot ring</li> <li>• Knocked down chair in carton</li> </ul>	<ul style="list-style-type: none"> <li>• Seven arms: <ul style="list-style-type: none"> <li>- Fixed cantilever arms</li> <li>- Fixed "T" arms</li> <li>- Height and width adjustable arms</li> <li>- Height adjustable arms</li> <li>- Height adjustable arms - black/chrome</li> <li>- Height and width adjustable arms - black/chrome</li> </ul> </li> <li>• Counter or bar height</li> <li>• Three lined mesh colors: Black, dark grey, silver</li> <li>• Adjustable lumbar support</li> <li>• Glides or soft wheel casters</li> <li>• Fully assembled chair in carton</li> </ul>

## Standard textile selection

<https://ofs.com/resources/textiles>

## Frame construction

Seat	<ul style="list-style-type: none"> <li>• <math>\frac{5}{8}</math>" One-piece multi-core hardwood plywood</li> <li>• Fitted with riveted "T" nuts fixed on both sides of the plywood</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Plastic: polypropylene and nylon</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• Mesh: elastomer (hytrel) and polyester fiber content</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• Fixed cantilever arms</li> <li>• Fixed "T" arms</li> <li>• Height adjustable arms</li> <li>• Height and width adjustable arms</li> <li>• Height adjustable arms - black/chrome</li> <li>• Height and width adjustable arms - black/chrome</li> </ul>
Controls	<ul style="list-style-type: none"> <li>• PSA5 control</li> </ul>
Base	<ul style="list-style-type: none"> <li>• Fiberglass solid injection-molded, glass-reinforced nylon resin</li> <li>• All bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>• Variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>• Nylon twin wheel casters manufactured of injection-molded engineer grade nylon</li> <li>• 60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>• 3D molded foam</li> <li>• 2.5 Density</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
------	---