



Counter height stool 4119

Overall dimensions	28.5"w x 28.5"d x 39.75/49.75"h	Weight	52 lbs. Armless 59 lbs. Arms	
Seat dimensions	20.75"w x 18.5"d x 19/26.5"h	Cubic feet	12.75	
Seat to top of back	24.5"	COM	1.5 yds. FoamMesh	
Back width	20.25"	COL	30 sq. ft. FoamMesh	
Top of arm to floor	24.5/33" (CR11), 24.25/32.5" (CR12), 25/30.25" (CR14), 27.75/39.75" (CR31), 27.25/39.5" (CR32)			
Top of arm to seat	8/11" (CR11), 7.5/10.5" (CR12), 8" (CR14), 7/11" (CR31), 6.5/10.5" (CR32)			

Bar height stool 4119

Overall dimensions	28.5"w x 28.5"d x 43.5/56"h	Weight	53 lbs. Armless 60 lbs. Arms	
Seat dimensions	20.75"w x 18.5"d x 22.75/32.75"h	Cubic feet	12.75	
Seat to top of back	20.75/23.25"	COM	1.5 yds. FoamMesh	
Back width	20.25"	COL	30 sq. ft. FoamMesh	
Top of arm to floor	28.5/39.25" (CR11), 28/38.75" (CR12), 28.75/36.5" (CR14), 31.5/46" (CR31), 31/45.5" (CR32)			
Top of arm to seat	8/11" (CR11), 7.5/10.5" (CR12), 8" (CR14), 7/11" (CR31), 6.5/10.5" (CR32)			

Standard features	Options available
<ul style="list-style-type: none"> • Armless • FoamMesh outer back • Upholstered seat • Molded seat and back foam • 20" Foot ring • Black nylon base • Hard wheel casters • ANSI/BIFMA X5.1 • CAL TB 117-2013 Conformant 	<ul style="list-style-type: none"> • Heavy Duty option • Five arms: <ul style="list-style-type: none"> - Height adjustable arms - Height and width adjustable arms - Fixed cantilever arms - Angled height adjustable arms - Angled height and width adjustable arms • Counter or bar height • Posture back with internal back height adjustment • Polished aluminum base • Black Ballistic nylon outer back or fully upholstered back • Soft wheel casters with safety brakes • Soft wheel casters • Glides • Fully assembled chair in carton • CAL TB 133 Conformant



Standard textile selection

<https://ofs.com/resources/textiles>

- All textiles meet CAL TB 117-2013

Frame construction

Seat	<ul style="list-style-type: none">• 5/8" One-piece, multi-core hardwood plywood• Fitted with riveted "T" nuts fixed on both sides of the plywood
Back	<ul style="list-style-type: none">• Polypropylene and nylon
Arms	<ul style="list-style-type: none">• Height Adjustable Arms• Height and Width Adjustable Arms• Fixed Cantilever Arms• Height Adjustable Arms• Height and Width Adjustable Arms• Heavy-Duty Height Adjustable Arms• Heavy-Duty Height and Width Adjustable Arms
Controls	<ul style="list-style-type: none">• PSAS – Posture Back with Seat Slider: single lever controls, back only (fixed seat)• HSAS – Heavy-Duty with Seat Slider: single lever controls, back only (fixed seat)
Base	<ul style="list-style-type: none">• Nylon: solid injection-molded and glass-reinforced nylon resin• Polished Aluminum: manufactured of die-casting process• All Bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none">• Variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none">• Heavy-Duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon• 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none">• Self-locking, hardened steel, Hex/Socket/Phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration

Foam

Seat/back	<ul style="list-style-type: none">• 3D Molded foam• 2.5 lb. Density• CAL TB 117-2013 Product Specifications
-----------	---