

**Mid mesh back task 3607M**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	<b>Weight</b>	40.75 lbs. Armless 44.7 lbs. Arms (CR13) 45 lbs. Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16/20"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	21.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	18.5"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**Mid upholstered back task 3607**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	<b>Weight</b>	42.75 lbs. Armless 46.75 lbs Arms (CR13) 47 lbs Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16/20"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	21.25"	<b>COM</b>	1.25 yds.	
<b>Back width</b>	18.5"	<b>COL</b>	25 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**Mid impression back task 3607T**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	<b>Weight</b>	41.75 lbs. Armless 46 lbs. Arms (CR20) 45.75 lbs Arms (CR13)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16/20"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	21.25"	<b>COM</b>	1 yds.	
<b>Back width</b>	18.5"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

Standard features	Options available
<ul style="list-style-type: none"> <li>• Mid back</li> <li>• Tailored seat</li> <li>• Armless</li> <li>• Carbon frame</li> <li>• Synchro tilt control with side tension knob</li> <li>• Upholstered seat with molded seat foam</li> <li>• Carbon nylon base</li> <li>• Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>• Mesh, upholstered or impression back</li> <li>• Arms: <ul style="list-style-type: none"> <li>- 4D pivoting arms</li> <li>- Polished aluminum cantilever arms</li> </ul> </li> <li>• Seven mesh colors: blue, deep blue, grey, pitch, platinum, poppy, snow or storm</li> <li>• Two impression colors: pitch or platinum</li> <li>• Body balance control</li> <li>• Seat slider</li> <li>• Adjustable lumbar support</li> <li>• Polished aluminum base</li> <li>• Adjustable headrest</li> <li>• Soft wheel casters or glides</li> <li>• Fully assembled chair in carton</li> </ul>

## Standard textile selection

<https://ofs.com/resources/textiles>

## Frame construction

Seat	<ul style="list-style-type: none"> <li>• 5/8" One-piece, multi-core hardwood plywood</li> <li>• Fitted with riveted "T" nuts fixed on both sides of the plywood</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polypropylene and nylon: carbon</li> <li>• Mesh: 40% elastomer, 60% polyester</li> <li>• Impression: inner foam laminated with polyester fabric on both sides, a line design is pressed into material</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• Mesh: 100% high tenacity polyester breathable material that curves across the chair back</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• 4D pivoting arms</li> <li>• Fixed cantilever aluminum arms</li> </ul>
Head rest	<ul style="list-style-type: none"> <li>• Material is FoamMesh or upholstery to match seat</li> <li>• Added height to chair = 6"/ 9.25", range of upholstered pad = 1.5"</li> </ul>
Lumbar support	<ul style="list-style-type: none"> <li>• Matches frame color</li> <li>• Height from seat = 5.25"/ 8.25", Range = 3"</li> </ul>
Controls	<ul style="list-style-type: none"> <li>• STT8 - Synchro tilt with side tension knob: adjusts to user's body weight and can tilt free or lock in three positions - optional SS3 seat slider</li> <li>• BDB4 - Body balance: weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 2 position limiter, tension control, back height adjustment - optional SS3 seat slider</li> </ul>
Seat Slider	<ul style="list-style-type: none"> <li>• Range: 2.25"</li> <li>• 5 Locking positions</li> </ul>
Base	<ul style="list-style-type: none"> <li>• Nylon: solid injection-molded and fiber glass-reinforced nylon resin - carbon</li> <li>• Polished aluminum: manufactured of die-casting process</li> <li>• All bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>• Heavy-duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>• 60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>• 3D molded foam</li> <li>• 40 IFD</li> <li>• 2 lb. Density</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
------	---

**High mesh back task 3615M**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	<b>Weight</b>	41.5 lbs. Armless 45.5 lbs. Arms (CR13) 45.75 lbs. Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**High elastomer back task 3615E**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	<b>Weight</b>	43.25 lbs. Armless 47.75 lbs. Arms (CR13) 47.25 lbs. Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19 d x 16/20"h (BDB4)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**High upholstered back task 3615**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	<b>Weight</b>	43.5 lbs. Armless 47.5 lbs. Arms (CR13) 47.75 lbs. Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1.25 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	25 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**High impression back task 3615T**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	<b>Weight</b>	42.5 lbs. Armless 46.5 lbs. Arms (CR13) 46.75 lbs. Arms (CR20)	
<b>Seat dimensions</b>	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yds.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

Standard features	Options available
<ul style="list-style-type: none"> <li>High back</li> <li>Upholstered back will have black mesh backer (3615)</li> <li>Tailored seat</li> <li>Armless</li> <li>Synchro tilt control with side tension knob</li> <li>Upholstered seat with molded seat foam</li> <li>Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>Mesh, elastomer, impression or upholstered back</li> <li>Black, graphite or chalk frame (Note: base, arm extension and seat pan match frame color)</li> <li>Arms: <ul style="list-style-type: none"> <li>4D pivoting arms</li> <li>Polished aluminum cantilever arms</li> </ul> </li> <li>Seven mesh colors: blue, deep blue, grey, pitch, platinum, poppy, snow or storm</li> <li>Eight elastomer colors: clay, sage, oat, deep blue, pitch, platinum, snow or storm</li> <li>Two impression colors: pitch or platinum</li> <li>Body balance control</li> <li>Seat slider</li> <li>Adjustable lumbar support: black, graphite or chalk (matches frame choice)</li> <li>Polished aluminum base</li> <li>Adjustable headrest</li> <li>Soft wheel casters or glides</li> <li>Fully assembled chair in carton</li> </ul>

### Standard textile selection

<https://ofs.com/resources/textiles>

### Frame construction

Seat	<ul style="list-style-type: none"> <li>5/8" One-piece, multi-core hardwood plywood</li> <li>Fitted with riveted "T" nuts fixed on both sides of the plywood</li> </ul>
Back	<ul style="list-style-type: none"> <li>Polypropylene and nylon: carbon, graphite and chalk</li> <li>Mesh: 40% elastomer, 60% polyester</li> <li>Elastomer: thermoplastic polyurethane</li> <li>Impression: inner foam laminated with polyester fabric on both sides, a line design is pressed into material</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>Mesh: 100% high tenacity polyester breathable material that curves across the chair back</li> </ul>
Arms	<ul style="list-style-type: none"> <li>4D pivoting arms</li> <li>Fixed cantilever aluminum arms</li> </ul>
Head rest	<ul style="list-style-type: none"> <li>Material is FoamMesh or upholstery to match seat</li> <li>Added height to chair = 6" / 9.25", range of upholstered pad = 1.5"</li> </ul>
Lumbar support	<ul style="list-style-type: none"> <li>Matches frame color choice</li> <li>Height from seat = 5.25" / 8.25", Range = 3"</li> </ul>
Controls	<ul style="list-style-type: none"> <li>STT8 - Synchro tilt with side tension knob: adjusts to user's body weight and can tilt free or lock in three positions - optional SS3 seat slider</li> <li>BDB4 - Body balance: weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 2 position limiter, tension control, back height adjustment - optional SS3 seat slider</li> </ul>
Seat slider	<ul style="list-style-type: none"> <li>Range: 2.25"</li> <li>5 Locking positions</li> </ul>
Base	<ul style="list-style-type: none"> <li>Nylon: solid injection-molded and fiber glass-reinforced nylon resin - carbon, graphite or chalk</li> <li>Polished aluminum: manufactured of die-casting process</li> <li>All bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>Heavy-duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>Self-locking, hardened steel, hex/socket/Phillips head bolts</li> <li>Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> </ul>

### Foam

Seat	<ul style="list-style-type: none"> <li>3D molded foam</li> <li>40 IFD</li> <li>2 lb. Density</li> <li>CAL TB 117-2013 Conformant</li> </ul>
------	---

**Mesh back task 3703M - BST4**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 31.25/36.25"h	<b>Weight</b>	32 lbs. Armless 33 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 15.25/20.25"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.25/29.25"			
<b>Top of arm to seat</b>	7.5"			

**Mesh back task 3703M - SWT2**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 31.5/36.25"h	<b>Weight</b>	34 lbs. Armless 35 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 15.5/20.5"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.75/29.75"			
<b>Top of arm to seat</b>	7.5"			

**Mesh back task 3703M - SWT4**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 32/37"h	<b>Weight</b>	33.75 lbs. Armless 35 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 15.75/20.75"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	25/30"			
<b>Top of arm to seat</b>	7.5"			

**Upholstered back task 3703 - BST4**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 31.25/36.25"h	<b>Weight</b>	32.5 lbs. Armless 33.5 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 17"d x 15.25/20.25"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.25/29.25"			
<b>Top of arm to seat</b>	7.5"			

**Upholstered back task 3703 - SWT2**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 31.5/36.5"h	<b>Weight</b>	34.5 lbs. Armless 35.5 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 17"d x 15.5/20.5"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	24.75/29.75"			
<b>Top of arm to seat</b>	7.5"			

**Upholstered back task 3703 - SWT4**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 32/37"h	<b>Weight</b>	34.25 lbs. Armless 35.5 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 17"d x 15.75/20.75"h	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	25/30"			
<b>Top of arm to seat</b>	7.5"			

## Impression back task 3703T

<b>Overall dimensions</b>	27.5"w x 27.5"d x 31.25/36.25"h (BST4) 27.5"w x 27.5"d x 31.5/36.5"h (SWT2) 27.5"w x 27.5"d x 32/27"h (SWT4)	<b>Weight</b>	32.25 lbs. Armless(BST4) 34.25 lbs. Armless (SWT2) 34 lbs. Armless (SWT4) 33.25 lbs. Arms (BST4) 35.25 lbs. Arms (SWT2) 35.25 lbs Arms (SWT4)
<b>Seat dimensions</b>	19.25"w x 18"d x 15.25/20.25"h (BST4) 19.25"w x 18"d x 15.5/20.5"h (SWT2) 19.25"w x 18"d x 15.75/20.75"h (SWT4)	<b>Cubic feet</b>	12.75
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.
<b>Top of arm to floor</b>	24.25/29.25" (BST4) 24.75/29.75" (SWT2) 25/30" (SWT4)		
<b>Top of arm to seat</b>	7.5"		



Standard features	Options available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• Basic task control</li> <li>• Upholstered seat with molded seat foam</li> <li>• Carbon nylon base</li> <li>• Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>• Mesh, impression or upholstered back</li> <li>• Black or silver frame</li> <li>• Seven mesh colors: blue, deep blue, grey, pitch, platinum, poppy, snow or storm</li> <li>• Two impression colors: pitch or platinum</li> <li>• Fixed arms (black only)</li> <li>• Controls: <ul style="list-style-type: none"> <li>- SWT2 swivel tilt</li> <li>- SWT4 swivel tilt</li> </ul> </li> <li>• Polished aluminum base</li> <li>• Soft wheel casters</li> <li>• Glides</li> <li>• Fully assembled chair in carton</li> </ul>

## Standard textile selection

<https://ofs.com/resources/textiles>


## Frame construction

Seat	<ul style="list-style-type: none"> <li>• Polypropylene</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polypropylene and nylon.</li> <li>• Mesh: 40% elastomer, 60% polyester</li> <li>• Impression: inner foam laminated with polyester fabric on both sides, a line design is pressed into material</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• Mesh: 100% high tenacity polyester breathable material that curves across the chair back</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• Fixed arms</li> </ul>
Controls	<ul style="list-style-type: none"> <li>• BST4 - Basic task: seat height adjustment</li> <li>• SWT2 - Swivel tilt: seat height adjustment, seat and back tilt adjustment and tension control</li> <li>• SWT4 - Swivel tilt: tilt seat, seat height adjustment</li> </ul>
Base	<ul style="list-style-type: none"> <li>• Nylon: solid injection-molded and glass-reinforced nylon resin</li> <li>• Polished aluminum: manufactured of die-casting process</li> <li>• All bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>• Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>• 60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/Phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> <li>• Back and seat are held together with upholstery clips</li> </ul>


## Foam

Seat	<ul style="list-style-type: none"> <li>• 3D molded foam</li> <li>• 5.58 lb. Density</li> <li>• 36 IFD</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
------	--


**Mesh back conference task 3705M**

<b>Overall dimensions</b>	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25"d x 34"h (SWT3)	<b>Weight</b>	32 lbs. Armless (BST4) 33.25 lbs. Arms (SWT3) 33.5 lbs. Armless (BST4) 34.75 lbs. Arms (SWT3)	
<b>Seat dimensions</b>	19.25"w x 18"d x 18"h (BST4) 19.25"w x 18"d x 18.25"h (SWT3)	<b>Cubic feet</b>	10.5	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	26.25" (BST4) 27" (SWT3)			
<b>Top of arm to seat</b>	7.5"			

**Upholstered back conference task 3705**

<b>Overall dimensions</b>	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25"d x 34"h (SWT3)	<b>Weight</b>	32.5 lbs. Armless (BST4) 33.75 lbs. Arms (BST4) 34 lbs. Armless (SWT3) 35.25 lbs. Arms (SWT3)	
<b>Seat dimensions</b>	19.25"w x 17"d x 18"h (BST4) 19.25"w x 17"d x 18.25"h (SWT3)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	26.25" (BST4) 27" (SWT3)			
<b>Top of arm to seat</b>	7.5"			

**Impression back conference task 3705T**

<b>Overall dimensions</b>	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25D x 34"h (SWT3)	<b>Weight</b>	32.25 lbs. Armless(BST4) 33.5 lbs. Arms (BST4) 33.5 lbs. Armless (SWT3) 35 lbs. Arms (SWT3)	
<b>Seat dimensions</b>	19.25"w x 18"d x 18"h (BST4) 19.25"w x 18"d x 18.25"h (SWT3)	<b>Cubic feet</b>	10.5	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	26.25" (BST4) 27" (SWT3)			
<b>Top of arm to seat</b>	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• Basic task control</li> <li>• Upholstered seat with molded seat foam</li> <li>• Polished aluminum 4-star base</li> <li>• High glides</li> </ul>	<ul style="list-style-type: none"> <li>• Mesh, impression or upholstered back</li> <li>• Seven mesh colors: blue, deep blue, grey, pitch, platinum, poppy, snow or storm</li> <li>• Two impression colors: pitch or platinum</li> <li>• Black or silver frame</li> <li>• Fixed arms (black only)</li> <li>• Control: basic swivel</li> <li>• Fully assembled chair in carton</li> </ul>



---

**Standard textile selection**

---

<https://ofs.com/resources/textiles>

---

**Frame construction**

---

- |            |   |
|------------|---|
| Seat       | <ul style="list-style-type: none"><li>• Polypropylene</li></ul>   |
| Back       | <ul style="list-style-type: none"><li>• Polypropylene and nylon.</li><li>• mesh: 40% elastomer, 60% polyester</li><li>• Impression: inner foam laminated with polyester fabric on both sides, a line design is pressed into material</li></ul>  |
| Upholstery | <ul style="list-style-type: none"><li>• Mesh: 100% high tenacity polyester breathable material that curves across the chair back</li></ul>  |
| Arms       | <ul style="list-style-type: none"><li>• Fixed arms</li></ul>  |
| Controls   | <ul style="list-style-type: none"><li>• BST4 - Basic control suitable for general office tasking and occasional typing or computer use</li><li>• SWT3 - Basic swivel control, basic control suitable for general office tasking and occasional typing or computer use</li></ul>                   |
| Base       | <ul style="list-style-type: none"><li>• Four-star polished aluminum base</li></ul>  |
| Cylinder   | <ul style="list-style-type: none"><li>• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li></ul>   |
| Glides     | <ul style="list-style-type: none"><li>• Nylon<ul style="list-style-type: none"><li>- Height from seat: 1 1/4" h x 2" diameter base</li><li>- 7/16" D-ring stem</li></ul></li></ul>  |
| Assembly   | <ul style="list-style-type: none"><li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li><li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li><li>• Back and seat are held together with upholstery clips</li></ul> |

---

**Foam**


---

- |      |   |
|------|---|
| Seat | <ul style="list-style-type: none"><li>• 3D molded foam</li><li>• 5.58 lb. Density</li><li>• 36 IFD</li><li>• CAL TB 117-2013 Conformant</li></ul> |
|------|---|



## Light task 3805

<b>Overall dimensions</b>	27.5"w x 27.5"d x 28.5/33.75"h (BST4) 27.5"w x 27.5"d x 29.5/34.75"h (SWT2)	<b>Weight</b>	33.5 lbs. Armless (BST4) 36.5 lbs. Arms (SWT2) 35.5 lbs. Armless (BST4) 38.75 lbs. Arms (SWT2)
<b>Seat dimensions</b>	17.75"w x 17.5"d x 14.75/20"h (plastic) 18.5"w x 17.75"d x 15.5/20.75"h (upholstered)	<b>Cubic feet</b>	12.75
<b>Seat to top of back</b>	12.75"	<b>COM</b>	1 yd.
<b>Back width</b>	18"	<b>COL</b>	20 sq. ft.
<b>Top of arm to floor</b>	22.25/27.5"		
<b>Top of arm to seat</b>	7.5"		



Standard features	Options available
<ul style="list-style-type: none"> <li>Molded plastic back</li> <li>Armless</li> <li>Basic task control</li> <li>Black nylon base</li> <li>Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>Graphite or chrome frame</li> <li>Fixed arms (arm colors match plastic)</li> <li>Plastic or upholstered seat with molded seat foam or plastic seat</li> <li>Five plastic colors: deep blue, pitch, platinum, snow or storm</li> <li>Control: swivel tilt</li> <li>Fully assembled chair in carton</li> <li>Soft wheel casters</li> <li>Glides</li> <li>Polished aluminum base</li> </ul>

## Standard textile selection

<https://ofs.com/resources/textiles>

## Frame construction

Seat	<ul style="list-style-type: none"> <li>Polypropylene</li> </ul>
Back	<ul style="list-style-type: none"> <li>Polypropylene</li> </ul>
Arms	<ul style="list-style-type: none"> <li>Fixed arms with polypropylene arm caps</li> </ul>
Controls	<ul style="list-style-type: none"> <li>BST4 - Basic task: seat height adjustment</li> <li>SWT2 - Swivel tilt: seat height adjustment, seat and back tilt adjustment and tension control</li> </ul>
Base	<ul style="list-style-type: none"> <li>Nylon: solid injection-molded and glass-reinforced nylon resin</li> <li>Polished aluminum: manufactured of die-casting process</li> <li>All bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>3D molded foam</li> <li>58 IFD</li> <li>5.14 Density</li> <li>CAL TB 117-2013 Conformant</li> </ul>
------	--