




Mesh Mid Back Task 1506 - SWT2 (Swivel Tilt Control)

Overall Dimensions	27.5"w x 27.5"d x 36.25/42.5"h	Weight	38 lbs. Armless 44.5 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16.5/20.5"h	Cubic Feet	14.5	
Seat to Top of Back	20.25/22.25"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26.25/30" (CR10), 24/31" (CR11), 23.75/30.5" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Mesh Mid Back Task 1506 - BST1 (Basic Synchro Tilt Control)


Overall Dimensions	27.5"w x 27.5"d x 35.25/41.5"h	Weight	40 lbs. Armless 46.5 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16.5/20.5"h	Cubic Feet	14.5	
Seat to Top of Back	19.25/21.25"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26/30" (CR10), 24/31" (CR11), 23.75/30.5" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Mesh Mid Back Task 1506 - BDB3 (Body Balance Control)


Overall Dimensions	27.5"w x 27.5"d x 35.5/41.75"h	Weight	42 lbs. Armless 48.5 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16/20"h	Cubic Feet	14.5	
Seat to Top of Back	19.25/21.25"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26/31.75" (CR10), 24/31.25" (CR11), 23.75/30.75" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Standard Features	Options Available
<ul style="list-style-type: none"> • Mid back • Mesh back • Armless • Swivel Tilt Control • Upholstered seat with molded seat foam • Internal back height adjustment • Black nylon base • Hard wheel casters • 300 lbs. weight rated • ANSI/BIFMA X5.1 • CAL TB 117-2013 Conformant 	<ul style="list-style-type: none"> • Three arms: <ul style="list-style-type: none"> - Fixed Arms - Height Adjustable Arms - Height and Width Adjustable Arms • Two controls: <ul style="list-style-type: none"> - Basic Synchro Tilt - Body Balance • Seven mesh colors: deep blue, oasis, pitch, platinum, scarlet, snow, storm • Seat slider • Polished aluminum base • Soft wheel casters • Glides • Fully assembled chair in carton • CAL TB 133 Conformant


Mesh High Back Task 1510 - SWT2 (Swivel Tilt Control)

Overall Dimensions	27.5"w x 27.5"d x 38.5/44.75"h	Weight	38 lbs. Armless 45 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16.5/20.5"h	Cubic Feet	14.5	
Seat to Top of Back	22.5/24.5"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26.25/30" (CR10), 24/31" (CR11), 23.75/30.5" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Mesh High Back Task 1510 - BST1 (Basic Synchro Tilt Control)

Overall Dimensions	27.5"w x 27.5"d x 37.75/44"h	Weight	40 lbs. Armless 47 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16.5/20.5"h	Cubic Feet	14.5	
Seat to Top of Back	21.75/23.75"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26/30" (CR10), 24/31" (CR11), 23.75/30.5" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Mesh High Back Task 1510 - BDB3 (Body Balance Control)

Overall Dimensions	27.5"w x 27.5"d x 38/44.25"h	Weight	42 lbs. Armless 49 lbs. Arms	
Seat Dimensions	20"w x 19.25"d x 16/20"h	Cubic Feet	14.5	
Seat to Top of Back	22/24"	COM	1 yd.	
Back Width	18.25"	COL	19 sq. ft.	
Top of Arm to Floor	26/31.75" (CR10), 24/31.25" (CR11), 23.75/30.75" (CR12)			
Top of Arm to Seat	9" (CR10), 7/10" (CR11), 6/9" (CR12)			

Standard Features	Options Available
<ul style="list-style-type: none"> • High back • Mesh back • Armless • Swivel Tilt Control • Upholstered seat with molded seat foam • Internal back height adjustment • Black nylon base • Hard wheel casters • 300 lbs. weight rated • ANSI/BIFMA X5.1 • CAL TB 117-2013 Conformant 	<ul style="list-style-type: none"> • Three arms: <ul style="list-style-type: none"> - Fixed Arms - Height Adjustable Arms - Height and Width Adjustable Arms • Two controls: <ul style="list-style-type: none"> - Basic Synchro Tilt - Body Balance • Seven mesh colors: deep blue, oasis, pitch, platinum, scarlet, snow, storm • Seat slider • Polished aluminum base • Soft wheel casters • Glides • Fully assembled chair in carton • CAL TB 133 Conformant



Standard Textile Selection

- <https://ofs.com/resources/textiles>
- All textiles meet CAL TB 117-2013

Frame Construction

- | | |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Seat | <ul style="list-style-type: none">• ½" Multi-core hardwood plywood• Fitted with riveted "T" nuts fixed on both sides of the plywood |
| Back | <ul style="list-style-type: none">• Polypropylene and nylon |
| Upholstery | <ul style="list-style-type: none">• Mesh: 100% High tenacity polyester |
| Arms | <ul style="list-style-type: none">• Fixed• Height Adjustable• Height and Width Adjustable |
| Controls | <ul style="list-style-type: none">• SWT2 - Swivel Tilt: seat height adjustment, seat and back tilt adjustment, tension control, back height adjustment• BST1 - Basic Synchro Tilt: seat height adjustment, tension control, back height adjustment, synchronized seat and back tilt adjustment - optional SS3 Seat Slider• BDB3 - Body Balance: weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 3 position limiter, tension control, back height adjustment - optional SS3 Seat Slider |
| Base | <ul style="list-style-type: none">• Fiberglass solid injection-molded, glass-reinforced nylon resin• Polished Aluminum: manufactured of die-casting process• All bases pass the ANSI/BIFMA strength standards |
| Cylinder | <ul style="list-style-type: none">• Variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria |
| Casters | <ul style="list-style-type: none">• Nylon twin wheel casters manufactured of injection-molded engineer grade nylon• 60 mm diameter large pivot barrels |
| Assembly | <ul style="list-style-type: none">• Self-locking, hardened steel, Hex/Socket/Phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration |

Foam

- | | |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Seat | <ul style="list-style-type: none">• 2" 3D Molded foam• 1.9 Density• 34 IFD• CAL TB 117-2013 Conformant |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------|