Pret stool

High back counter stool with arms and Nylon base 86057

Overall dimensions	26.75″w x 25″d x 43.75/51.25″h	**Weight**	33.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 22.5/30″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		
Top of arm to floor	32/39.5″		
Top of arm to seat	8.5″		



High back counter stool with arms and Polished Aluminum base 86057

Overall dimensions	26.75″w x 25″d x 43.25/50.75″h	**Weight**	35.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 22.25/29.75″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		
Top of arm to floor	31.5/39″		
Top of arm to seat	8.5″		



High back bar stool with arms and Nylon base 86057

Overall dimensions	26.75″w x 25″d x 47.5/57.5″h	**Weight**	34.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 26/36″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		
Top of arm to floor	35.75/45.75″		
Top of arm to seat	8.5″		



High back bar stool with arms and Polished Aluminum base 86057

Overall dimensions	26.75″w x 25″d x 47/57″h	**Weight**	36.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 25.5/35.5″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		
Top of arm to floor	35.25/45.25″		
Top of arm to seat	8.5″		



Standard features	Options available
• Fixed loop arm • One-piece mesh seat and back • Body balance control • Hard wheel casters • Nylon base • 20″ Foot ring • ANSI/BIFMA X5.1 Conformant • CAL TB 117-2013 Conformant	• Four mesh colors: dove, granite, ocean, raven • Carbon, chalk or graphite frame • Carbon, chalk or graphite nylon base • Polished aluminum base • 8″ CHC or 10″ BHC cylinder • Soft wheel casters • Glides • Fully assembled chair in carton

High back counter stool armless with Nylon base 86157

Overall dimensions	26.75″w x 25″d x 43.75/51.25″h	**Weight**	33.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 22.5/30″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		
Top of arm to floor	32/39.5″		
Top of arm to seat	8.5″		



High back counter stool armless with Polished Aluminum base 86157

Overall dimensions	26.75″w x 25″d x 43.25/50.75″h	**Weight**	35.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 22.25/29.75″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		



High back bar stool armless with Nylon base 86157

Overall dimensions	26.75″w x 25″d x 47.5/57.5″h	**Weight**	34.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 26/36″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		



High back bar stool armless with Polished Aluminum base 86157

Overall dimensions	26.75″w x 25″d x 47/57″h	**Weight**	36.6 lbs.
Seat dimensions	19.75″w x 17.5″d x 25.5/35.5″h	**Cubic feet**	22
Seat to top of back	22″		
Back width	19″		



Standard features	Options available
• Fixed loop arm • One-piece mesh seat and back • Body balance control • Hard wheel casters • Nylon base • 20″ Foot ring • ANSI/BIFMA X5.1 Conformant • CAL TB 117-2013 Conformant	• Four mesh colors: dove, granite, ocean, raven • Carbon, chalk or graphite frame • Carbon, chalk or graphite nylon base • Polished aluminum base • 8″ CHC or 10″ BHC cylinder • Soft wheel casters • Glides • Fully assembled chair in carton

Frame construction

Shell	• Injection-molded, glass-reinforced nylon resin
Upholstery	• Mesh: woven polyester yarn and polyelastomer monofilament • All mesh colors conform to CAL tech bulletin 117-2013
Control	• Body balance: weight activated, adjusts to user's body weight • Rated up to 300 lbs. on all mechanisms
Base	• Nylon: solid injection-molded and glass-reinforced nylon resin • Polished aluminum: manufactured of die cast aluminum • All bases pass the ANSI/BIFMA strength and durability standards
Cylinder	• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria • 8″ (CHC) counter height stool cylinder • 10″ (BHC) bar height stool cylinder
Casters	• Twin wheel casters manufactured of injection-molded engineer grade nylon • 60 mm diameter large pivot barrels
Assembly	• Self-locking, hardened steel, slotted/Phillips head bolts • Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration