

Mesh back task chair 705M

Overall dimensions	26.5"w x 26.5"d x 31.25/36.5"h	Weight	34 lbs.
Seat dimensions	16"w x 19"d x 16.25/21.25"h	Cubic feet	12.75
Seat to top of back	16"	COM	1 yds.
Top of arm to floor	24.25"/29.25" (fixed arms CR10)	COL	20 sq. ft.
Top of arm to seat	8" (fixed arms CR10)		



Standard features	Options available
<ul style="list-style-type: none"> • Armless • Mesh back with upholstered seat • Black nylon base • Casters • All styles rated up to 300 lbs. 	<ul style="list-style-type: none"> • Frame in black or silver • Fixed arms available in black only • Basic task or swivel tilt • Black nylon or polished aluminum base • Glides, black hard wheel or soft wheel casters • Black, dark grey or silver mesh back • Additional seat foam • Fully assembled or knocked down

Mesh back mid height 715M

Overall dimensions	26.5"w x 26.5"d x 35.5/43.5"h	Weight	39 lbs.
Seat dimensions	16"w x 19"d x 20.5/28.56"h	Cubic feet	12.75
Seat to top of back	16"	COM	1 yds.
Top of arm to floor	29.75"/37.25" (fixed arms CR10)	COL	20 sq. ft.
Top of arm to seat	8" (fixed arms CR10)		


Mesh back counter height 715M

Overall dimensions	26"w x 26"d x 35.5/45.5"h	Weight	34.6 lbs.
Seat dimensions	17.75"w x 18"d x 22/31.75"h	Cubic feet	12.75
Seat to top of back	15"	COM	1 yds.
Top of arm to floor	33.75"/43.75" (fixed arms CR10)	COL	20 sq. ft.
Top of arm to seat	8" (fixed arms CR10)		



Standard features	Options available
<ul style="list-style-type: none"> • Armless • Mesh back • Molded seat foam • Basic task control • Black nylon base • 20" foot ring • Casters • All styles rated up to 300 lbs. 	<ul style="list-style-type: none"> • Frame in black or silver • Fixed arms available in black only • Black nylon or polished aluminum base • Mid or counter height • Glides, black hard wheel or soft wheel casters • Black, dark grey or silver mesh back • Additional seat foam • Fully assembled or knocked down



Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

Shell	<ul style="list-style-type: none">• Injection-molded, glass-reinforced nylon resin
Upholstery	<ul style="list-style-type: none">• Mesh: woven polyester yarn and polyelastomer monofilament• All mesh colors conform to CAL Tech Bulletin 117-2013
Arms	<ul style="list-style-type: none">• Fixed loop arms
Control	<ul style="list-style-type: none">• Body Balance: weight activated, adjusts to user's body weight
Base	<ul style="list-style-type: none">• Nylon: solid injection-molded and glass-reinforced nylon resin• Polished aluminum: manufactured of die cast aluminum• All bases pass the ANSI/BIFMA strength and durability standards
Cylinder	<ul style="list-style-type: none">• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none">• Twin wheel casters manufactured of injection-molded engineer grade nylon• 60 mm Diameter large pivot barrels
Assembly	<ul style="list-style-type: none">• Self-locking, hardened steel, slotted/Phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration