

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Case Construction

- 3/4" 3 ply (45 lb. substrate) laminate panel with 2mm PP banding case parts
- Case parts are precisely routed and bored on CNC machinery
- Dowel construction is primary method
- Cam lock construction is secondary method
- Structural joints are secured by 16 gauge steel angle brackets

Drawer Construction

- 5 piece method 1 front & 4 sided box with bottom
- 3/4" 3 ply (45 lb. substrate) laminate panel with 2mm PP banding fronts
- White vinyl drawer boxes use miter and dowel with glue construction
- White plastic removable insert liners are also available

Drawer Suspension

- Load capacity of 100 lbs.
- Soft close drawer slides
- Ball bearing rollers
- Limited lifetime warranty

Door Construction

- 3/4" 3 ply (45 lb. substrate) laminate panel with 2mm PVC banding
- 3 door hinge options in silver finish, 110 degree, concealed, soft close

Lock Options

- Locks can be added to top drawers or doors
- Key
- Electronic lock
- Mechanical lock,
- Padlock hasp
- All locks accept a master key or code

Glide/Base Completion

- Nylon screw-in levelers are on all base, storage, media & bench cabinets
- Cove base molding is required to complete installation (supplied and installed by others)
- 1" adjustable glide

HPL Top Construction

- 1" 3 ply (45 lb. substrate) laminate panel with PP or Self Edge banding
- 3/4" x 4" HPL backsplash
- Drop-in stainless steel sink option
- 4 paddle faucets, 3 sensor faucets
- Waste rings available in silver or black

Solid Surface Top Construction

- 1" built-up solid surface with MDF substrate panel, finished front edge & optional finished or seamable end edges
- 1/2" x 4" solid surface integrated backsplash and optional solid surface sidesplashes
- 3 sink options, drop -in or undermount stainless steel or integrated solid surface
- 4 paddle faucets, 3 sensor faucets
- 3 waste ring options; integrated, silver or black