

Low back stool 93055

Overall dimensions	28.5"w x 28.5"d x 37.25-44.5"h (CHC) 28.5"w x 28.5"d x 41-51.25"h (BHC)	Weight	28 lbs. (CHC) 29 lbs. (BHC)	
Seat dimensions	18"w x 18.25"d x 21.75-29"h (CHC) 18"w x 18.25"d x 25.5-35.5"h (BHC)	Cubic feet	11	
Seat to top of back	13"	COM	.75 yds.	
Top of arm to floor	29.25/36.5" (CHC) 33/43" (BHC)	COL	15 sq. ft.	
Top of arm to seat	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> Rated up to 300 lbs. Fixed arms Upholstered seat Molded plastic shell Polished aluminum 5-star base Polished gas cylinder 20" Foot ring 	<ul style="list-style-type: none"> Finish available in Carbon or Cloud <ul style="list-style-type: none"> Carbon frame with Carbon arm pads Cloud frame with grey arm pads Soft wheel casters Glides Fully assembled

Construction

Shell	<ul style="list-style-type: none"> The one-piece plastic shell is constructed of injection-molded, glass-reinforced nylon resin Carbon or Cloud finish option
Upholstery	<ul style="list-style-type: none"> All fabrics meet CAL Tech Bulletin 117-2013
Arms	<ul style="list-style-type: none"> Integrated, fixed cantilever arms with polypropylene arm pad Carbon frame with Carbon arm pads Cloud frame with grey arm pads
Controls	<ul style="list-style-type: none"> All purpose is rated up to 300 lbs Swivel tilt mechanism with height adjustment
Bases	<ul style="list-style-type: none"> 5 Star polished base is constructed from die cast aluminum and meets ANSI/BIFMA strength and durability requirements
Cylinder	<ul style="list-style-type: none"> Our variety of Class 4 gas cylinders, meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none"> Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon and contain 60mm diameter large pivot barrels.