




**High back mesh stool 3619M**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 44/51.5"h (CHC) 27.5"w x 27.5"d x 47.75/58"h (BHC)	<b>Weight</b>	49.5 lbs. Armless (CHC) 53.5 lbs. (CR13) Arms (CHC) 54 lbs. (CR20) Arms (CHC) 50.5 lbs. Armless (BHC) 53.25 lbs. (CR13) Arms (BHC) 55 lbs. (CR20) Arms (BHC)	
<b>Seat dimensions</b>	20.25"w x 19"d x 20.75/28.25"h (CHC) 20.25"w x 19"d x 24.25/34.25"h (BHC)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	29.5/40.75" (CR13) 30/38" (CR20) (CHC) 33/47" (CR13) 34/44" (CR20) (BHC)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			


**High back elastomer stool 3619E**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 44/51.5"h (CHC) 27.5"w x 27.5"d x 47.75/58"h (BHC)	<b>Weight</b>	51.5 lbs. Armless (CHC) 55.5 lbs. (CR13) Arms (CHC) 55.75 lbs. (CR20) Arms (CHC) 52.5 lbs. Armless (BHC) 56.5 lbs. (CR13) Arms (BHC) 56.75 lbs. (CR20) Arms (BHC)	
<b>Seat dimensions</b>	20.25"w x 19"d x 20.75/28.25"h (CHC) 20.25"w x 19"d x 24.25/34.25"h (BHC)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	29.5/40.75" (CR13) 30/38" (CR20) (CHC) 33/47" (CR13) 34/44" (CR20) (BHC)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**High back fully upholstered stool 3619**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 44/51.5"h (CHC) 27.5"w x 27.5"d x 47.75/58"h (BHC)	<b>Weight</b>	51.5 lbs. Armless (CHC) 55.5 lbs. (CR13) Arms (CHC) 56 lbs. (CR20) Arms (CHC) 52.5 lbs. Armless (BHC) 56.5 lbs. (CR13) Arms (BHC) 57 lbs. (CR20) Arms (BHC)	
<b>Seat dimensions</b>	20.25"w x 19"d x 20.75/28.25"h (CHC) 20.25"w x 19"d x 24.25/34.25"h (BHC)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1.25 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	25 sq. ft.	
<b>Top of arm to floor</b>	29.5/40.75" (CR13) 30/38" (CR20) (CHC) 33/47" (CR13) 34/44" (CR20) (BHC)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

**High back impression stool 3619T**

<b>Overall dimensions</b>	27.5"w x 27.5"d x 44/51.5"h (CHC) 27.5"w x 27.5"d x 47.75/58"h (BHC)	<b>Weight</b>	50.5 lbs. Armless (CHC) 54.5 lbs. (CR13) Arms (CHC) 55 lbs. (CR20) Arms (CHC) 51.5 lbs. Armless (BHC) 55.5 lbs. (CR13) Arms (BHC) 56 lbs. (CR20) Arms (BHC)	
<b>Seat dimensions</b>	20.25"w x 19"d x 20.75/28.25"h (CHC) 20.25"w x 19"d x 24.25/34.25"h (BHC)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	23.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.25"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	29.5/40.75" (CR13) 30/38" (CR20) (CHC) 33/47" (CR13) 34/44" (CR20) (BHC)			
<b>Top of arm to seat</b>	7/11" (CR13) 8" (CR20)			

Standard features	Options available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• High back</li> <li>• Tailored seat</li> <li>• Body balance control</li> <li>• Upholstered seat with molded seat foam</li> <li>• 20" Foot ring</li> <li>• Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>• Mesh, elastomer, impression or upholstered back</li> <li>• Carbon, graphite or chalk frame</li> <li>• Arms: <ul style="list-style-type: none"> <li>- 4D pivoting arms</li> <li>- Polished aluminum cantilever arms</li> </ul> </li> <li>• 2 Cylinder heights: CHC - counter height (8") or BHC - bar height (10")</li> <li>• Adjustable lumbar support: carbon, graphite or chalk (matches frame choice)</li> <li>• Sit-to-stand cylinder: <ul style="list-style-type: none"> <li>- STS1 G10 (7") 16.75/23.75 range with B17 base and 17/24" with B18 base</li> <li>- STS3 G15 (8") 18.5/26.5 range with B17 base and 19/27" with B18 base</li> <li>- STS4 G16 (9") 19.5/28.5" range with B17 base and 20/29" with B18 base</li> </ul> </li> <li>• Seven mesh colors: blue, deep blue, grey, pitch, platinum, or poppy, snow</li> <li>• Eight elastomer colors: clay, sage, oat, deep blue, pitch, platinum, snow or storm</li> <li>• Two impression colors: pitch, or platinum</li> <li>• Nylon base: carbon, graphite or chalk (matches frame choice)</li> <li>• Polished aluminum base</li> <li>• Soft wheel casters or glides</li> <li>• Fully assembled</li> </ul>

#### Standard textile selection

<https://ofs.com/resources/textiles>


#### Frame construction

Seat	<ul style="list-style-type: none"> <li>• 5/8" One-piece, multi-core hardwood plywood</li> <li>• Fitted with riveted "T" nuts fixed on both sides of plywood</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polypropylene and nylon: Black, graphite and chalk</li> <li>• Mesh: 40% elastomer, 60% polyester</li> <li>• Elastomer: thermoplastic polyurethane</li> <li>• Impression: inner foam laminated with polyester fabric on both sides, a line design is pressed into material</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• Mesh back is 100% high tenacity polyester breathable material</li> <li>• All fabrics meet CAL tech bulletin 117-2013</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• 4D pivoting arms</li> <li>• Fixed cantilever aluminum arms</li> </ul>
Lumbar support	<ul style="list-style-type: none"> <li>• Adjustable lumbar support: black, graphite or chalk (dependent on frame color choice)</li> <li>• Height from seat = 5.25"/8.25", Range = 3"</li> </ul>
Controls	<ul style="list-style-type: none"> <li>• R3 - body balance: weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 3 position limiter, tension control, back height adjustment</li> </ul>
Base	<ul style="list-style-type: none"> <li>• Nylon: solid injection-molded and glass-reinforced nylon resin - black, graphite or chalk</li> <li>• Polished aluminum: manufactured of die-casting process</li> <li>• All Bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>• Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>• 60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> </ul>


#### Foam

Seat	<ul style="list-style-type: none"> <li>• 3D molded foam</li> <li>• 40 IFD</li> <li>• 2 lb. Density</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polyurethane and nylon</li> </ul>


**Mesh back stool - counter height 3711M**

<b>Overall dimensions</b>	22.5"w x 25"d x 39.5"h	<b>Weight</b>	31 lbs. Armless 32.25 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 24.5"h	<b>Cubic feet</b>	17	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	32.75"			
<b>Top of arm to seat</b>	7.5"			


**Fully upholstered stool - counter height 3711**

<b>Overall dimensions</b>	22.5"w x 25"d x 39.5"h	<b>Weight</b>	31.5 lbs. Armless 32.75 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 24.5"h	<b>Cubic feet</b>	17	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1.75 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	35 sq. ft.	
<b>Top of arm to floor</b>	32.75"			
<b>Top of arm to seat</b>	7.5"			


**Impression back stool - counter height 3711T**

<b>Overall dimensions</b>	22.5"w x 25"d x 39.5"h	<b>Weight</b>	31.25 lbs. Armless 32.5 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 24.5"h	<b>Cubic feet</b>	17	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	32.75"			
<b>Top of arm to seat</b>	7.5"			


**Mesh back stool - bar height 3713M**

<b>Overall dimensions</b>	22.5"w x 25.5"d x 44.5"h	<b>Weight</b>	32.25 lbs. Armless 33.5 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 29.5"h	<b>Cubic feet</b>	22.5	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yd.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	37.75"			
<b>Top of arm to seat</b>	7.5"			

**Fully upholstered stool - bar height 3713**

<b>Overall dimensions</b>	22.5"w x 25.5"d x 44.5"h	<b>Weight</b>	32.75 lbs. Armless 34 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 29.5"h	<b>Cubic feet</b>	22.5	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1.75 yds.	
<b>Back width</b>	19.75"	<b>COL</b>	35 sq. ft.	
<b>Top of arm to floor</b>	37.75"			
<b>Top of arm to seat</b>	7.5"			

**Impression back stool - bar height 3713T**

<b>Overall dimensions</b>	22.5"w x 25.5"d x 44.5"h	<b>Weight</b>	33.5 lbs. Armless 33.75 lbs. Arms	
<b>Seat dimensions</b>	19.25"w x 18"d x 29.5"h	<b>Cubic feet</b>	22.5	
<b>Seat to top of back</b>	13.25"	<b>COM</b>	1 yds.	
<b>Back width</b>	19.75"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	37.75"			
<b>Top of arm to seat</b>	7.5"			



Standard features	Options available
<ul style="list-style-type: none"><li>• Armless</li><li>• Bar or counter height</li><li>• Upholstered seat with molded seat foam</li><li>• Nylon glides</li></ul>	<ul style="list-style-type: none"><li>• Mesh, impression or upholstered back</li><li>• Black or silver frame</li><li>• Fixed arms (black only)</li><li>• Seven mesh colors: blue, deep blue, grey, pitch, platinum, or poppy, snow</li><li>• Two impression colors: pitch, platinum or storm</li><li>• Felt tip glides</li></ul>

#### Standard textile selection

<https://ofs.com/resources/textiles>

#### Frame construction

Seat	<ul style="list-style-type: none"><li>• Polypropylene</li></ul>
Back	<ul style="list-style-type: none"><li>• Polypropylene and nylon</li></ul>
Upholstery	<ul style="list-style-type: none"><li>• Mesh: constructed of polyester, polyamid and elasthan fiber content</li><li>• Two part plastic back with upholstery clips</li><li>• All fabrics meet CAL Tech Bulletin 117-2013</li></ul>
Arms	<ul style="list-style-type: none"><li>• Fixed arms (black only)</li></ul>
Frame	<ul style="list-style-type: none"><li>• Rated up to 300 lbs.</li><li>• 7/8" Diameter 14 gage steel tubing</li><li>• Silver and black wall saver</li></ul>
Glides	<ul style="list-style-type: none"><li>• Nylon glides</li><li>• 1/8" high by 3/8" diameter base with a 1/2" stem</li></ul>
Assembly	<ul style="list-style-type: none"><li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li><li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li><li>• "NYLOK" fasteners semi-permanently secure all hardware seat &amp; back</li></ul>

#### Impression material

Back	<ul style="list-style-type: none"><li>• Constructed of three layers: inner foam laminated with polyester fabric on both sides.</li><li>• A line design is pressed into the material</li><li>• Color options: Pitch (TPI), Platinum (TPM) and Storm (TSM)</li><li>• CAL TB 117-2013 Conformant</li></ul>
------	---

#### Foam

Seat	<ul style="list-style-type: none"><li>• 3D molded foam</li><li>• 2.5 Density</li><li>• CAL TB 117-2013 Conformant</li></ul>
------	---

**Plastic back stool - counter height** 38111 (single) 38112 (double)

<b>Overall dimensions</b>	22"w x 23.5"d x 38.75"h	<b>Weight</b>	21 lbs.	
<b>Seat dimensions</b>	17.75"w x 17.75"d x 24.25"h (plastic) 18.5"w x 18"d x 25"h (upholstered)	<b>Cubic feet</b>	17	
<b>Seat to top of back</b>	12.75"	<b>COM</b>	1 yd.	
<b>Back width</b>	18"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	32"			
<b>Top of arm to seat</b>	7.5"			

**Plastic back stool - bar height** 38131 (single) 38132 (double)

<b>Overall dimensions</b>	22"w x 23.5"d x 43.75"h	<b>Weight</b>	21.75 lbs.	
<b>Seat dimensions</b>	17.75"w x 17.75"d x 29.25"h (plastic) 18.5"w x 18"d x 30"h (upholstered)	<b>Cubic feet</b>	17	
<b>Seat to top of back</b>	12.75"	<b>COM</b>	1 yd.	
<b>Back width</b>	18"	<b>COL</b>	20 sq. ft.	
<b>Top of arm to floor</b>	37"			
<b>Top of arm to seat</b>	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• Molded plastic back</li> <li>• Chrome wall saver frame</li> <li>• Counter height or bar height</li> <li>• Stacks two high</li> </ul>	<ul style="list-style-type: none"> <li>• Plastic or upholstered seat with molded seat foam</li> <li>• Five plastic colors: deep blue, pitch, platinum, or snow</li> <li>• Clear nylon glides</li> </ul>

**Standard textile selection**
<https://ofs.com/resources/textiles>
**Frame construction**

Seat	<ul style="list-style-type: none"> <li>• Polypropylene</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polypropylene</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• All fabrics meet CAL Tech Bulletin 117-2013</li> </ul>
Frame	<ul style="list-style-type: none"> <li>• Rated up to 300 lbs.</li> <li>• .441" Diameter steel rod and .157" steel plate</li> <li>• Chrome wall saver</li> </ul>
Glides	<ul style="list-style-type: none"> <li>• Nylon glides</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> <li>• "NYLOK" fasteners semi-permanently secure all hardware seat &amp; back</li> </ul>

**Foam**

Seat	<ul style="list-style-type: none"> <li>• 1" 3D molded foam</li> <li>• 5.14 Density</li> <li>• 58 IFD</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
------	---

## Plastic back light task stool - counter/bar height 3815

<b>Overall dimensions</b>	27.5"w x 27.5"d x 32.75/40.25"h (CHC) 27.5"w x 27.5"d x 43.75/56.25"h (BHC)	<b>Weight</b>	34 lbs. Armless 35 lbs. Arms (CHC) 37.25 lbs. Armless 38.25 lbs. Arms (BHC)	
<b>Seat dimensions</b>	17.75"w x 17.5"d x 18/25.5"h (CHC plastic) 18.5"w x 17.75"d x 18.75/26.25"h (CHC upholstered) 17.75"w x 17.5"d x 21.75/31.75"h (BHC plastic) 18.5"w x 17.75"d x 22.5/32.5"h (BHC upholstered)	<b>Cubic feet</b>	12.75	
<b>Seat to top of back</b>	22.75"	<b>COM</b>	1.25 yds.	
<b>Back width</b>	18"	<b>COL</b>	25 sq. ft.	
<b>Top of arm to floor</b>	26.25/33.75" (CHC), 30/40.25" (BHC)			
<b>Top of arm to seat</b>	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• Molded plastic back</li> <li>• Basic task control</li> <li>• Black nylon base</li> <li>• 20" Foot ring</li> <li>• Hard wheel casters</li> </ul>	<ul style="list-style-type: none"> <li>• Graphite or chrome frame</li> <li>• Fixed arms (arm colors match plastic back)</li> <li>• Plastic or upholstered seat with molded seat foam</li> <li>• 2 Cylinder heights: CHC - counter height (8") or BHC - bar height (10")</li> <li>• Five plastic colors: deep blue, pitch, platinum, or snow</li> <li>• Polished aluminum base</li> <li>• Soft wheel casters or glides</li> <li>• Fully assembled</li> </ul>

## Standard textile selection

<https://ofs.com/resources/textiles>

## Frame construction

Seat	<ul style="list-style-type: none"> <li>• Polypropylene</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Polypropylene</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• All fabrics meet CAL Tech Bulletin 117-2013</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• Fixed arms with polypropylene arm caps</li> </ul>
Frame	<ul style="list-style-type: none"> <li>• Rated up to 300 lbs.</li> <li>• .441" Diameter steel rod and .157" steel plate</li> <li>• Chrome wall saver</li> </ul>
Controls	<ul style="list-style-type: none"> <li>• T4 - basic task: seat height adjustment</li> </ul>
Base	<ul style="list-style-type: none"> <li>• Nylon: solid injection-molded and glass-reinforced nylon resin black</li> <li>• Polished aluminum: manufactured of die-casting process</li> <li>• All Bases pass the ANSI/BIFMA strength standards</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Glides	<ul style="list-style-type: none"> <li>• Nylon</li> </ul>
Casters	<ul style="list-style-type: none"> <li>• Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon</li> <li>• 60 mm diameter large pivot barrels</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Self-locking, hardened steel, hex/socket/phillips head bolts</li> <li>• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration</li> <li>• "NYLOK" fasteners semi-permanently secure all hardware seat &amp; back</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>• 1" 3D molded foam</li> <li>• 5.14 Density</li> <li>• 58 IFD</li> <li>• CAL TB 117-2013 Conformant</li> </ul>
------	---